



# ATLAS RESIN AWAY

## concentrated polymer dispersion residues remover

- removes residues of priming emulsions, paints and dispersion renders
- for ceramic, stone, clinker, chrome plated, varnished, stainless steel and plastic surfaces



### Use

**Removes residues of dispersions** – priming emulsions (e.g. ATLAS UNI-GRUNT), protective agents (e.g. ATLAS DELFIN), emulsion paints, dispersion renders.

**Types of cleaned surfaces** – ceramic (glazed, terracotta, porcelain, gres, clinker) and stone tiles, washing facilities, chrome-plated and varnished, stainless steel and plastic surfaces.

### Properties

**Fast and effective** – contains non-ionic surfactants, solvents and alkaline agents, dissolves dispersions quickly.

**Can be diluted** – depending on the degree of contamination, can be diluted with water (max. ratio 1:5).

### Technical data

ATLAS RESIN AWAY contains non-ionic surfactants, solvents and alkaline agents.

Density	approx. 1.0 g/cm <sup>3</sup>
Substrate and ambient temperature during work	from +5°C to +25°C

### Technical requirements

Cleaning agent is not classified as construction material.

### Cleaning

Depending on the degree of contamination - dilute ATLAS RESIN AWAY with water (max. ratio 1:5) and spread upon the surface. Strongly contaminated places should be soaked with undiluted agent. In either case leave soaked contamination for 15 minutes, so the agent starts to work, and remove the residues with a scrubbing brush then. Repeat the process, if necessary. Wash the whole surface thoroughly with water after cleaning.

### Consumption

The consumption depends on the degree and type of contamination.

### Important additional information

- The agent is not recommended for cleaning wooden surfaces and window panes. If in doubt conduct an application test before the main application of the agent.
- Wash the tools with clean water directly after use.
- Causes skin irritation. Causes serious eye irritation. Keep out of reach of children. Wear protective gloves/protective clothing/eye protection/face protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. IF ON SKIN: Wash with plenty of water with soap. If eye irritation persists get medical advice/attention. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing. Follow the instructions of the Safety Data Sheet.
- The agent must be transported and stored in tightly sealed packaging, in dry conditions and positive temperature. Protect against overheating. The emulsion shelf life is 12 months from the production date shown on the packaging.

### Packaging

Plastic drums: 1 kg  
Pallet: 576 kg in 1 kg drums.

*The above information constitutes basic guidelines for the application of the product and does not release the user from the obligation of carrying out works according to engineering principles and OHS regulations.  
At the time of publication of this product data sheet all previous ones become void.  
Date of update: 2022-01-04*